

Tailor made for VMware environments, the HP t310 Zero Client delivers amazing performance with the latest PCoIP VMware technology.



Tailor-made for VMware customers.

Don't hassle with set-up. This VMware ready, PC-over-IP zero client is ready to deploy and use right out of the box.

Reduce complexity with a zero client made specifically for VMware. Save time without the need to customize your fleet to VMware. You're ready to work.

Our best-performing PCoIP thin client.

Finish ahead of deadlines with fast boot and response times. Forget the lags.

See multimedia, online videos¹ and 3D applications running smoothly at native frame rates.

Expand your view. The HP t310 supports dual displays for multi-tasking and fine-tuning media projects.²

No local data storage. No space hog. True Zero Client.

Focus IT efforts on top priorities by cutting maintenance needs on desktops. Upgrade users quickly and inexpensively by updating application software hosted on servers.

Minimize the risks of your data getting into the wrong hands. With no data stored on the HP t310, your intellectual property stays on your secure server.

Boost security measures even more with the fiber network interface card (NIC).

Clear clutter from your desk. The small size (5.9 in/149.8 mm x 5.2 in/132.1 mm) keeps your work area free of distractions. You stay focused.

Warranty, service and support.

Easy setup, manageability and maintenance. Count on global service and support through a network of over 50,000 IT professionals in over 100 countries.

Worry less with a standard, three-year limited hardware warranty in most regions.

Choose from HP Care Pack Services³ to extend service contracts beyond your standard warranties.



Hardware Specifications	
Operating Systems	Completely operating system independent
Processor	TERA2321 PCoIP Zero Client processor
System memory	512 MB DDR3 1333 MHz SDRAM
Flash memory	256 MB SPI
Protocols	Teradici Optimized PCoIP
Monitor support	Supports up to 2 displays; 1 DVI-D, 1 DVI-I with resolutions up to 1920x1200 at 60Hz or single digital display at resolutions up to 2560x1600 using a custom DVI dual-link cable ⁴ .
Audio	1 microphone,1 headphone, 1 speaker
Communications	10/100/1000 BASE-T Ethernet (RJ-45) or 100 Mbps Fiber NIC, Wake on LAN (WoL) using magic packet
Ports and connectors	4 USB 2.0 (two in front, two in rear), 1 NIC (RJ-45), 1 power connector, 1 12VDC power Single-link DVI-D connector, Single-link DVI-I connector
Input devices	Keyboard USB and Mouse USB
Power	36 W AC adapter (12V DC) Worldwide auto-sensing 100-240 VAC, 50-60 Hz
Dimensions (WxDxH)	5.98 x 5.24 x 1.85 in (15.2 x 13.31 x 4.7 cm)
Weight	1.39 lbs (.63 kg)
Warranty	HP Total Care Warranty and Services: limited three-year hardware warranty in most regions. Optional HP Care Pack Services ^{3,5} extends service contracts beyond your standard warranties. For more details visit http://www.hp.com/qo/lookuptool .



HP t310 Zero Client

- 1. Internet access required.
- 2. Displays sold separately.
- 3. Service levels and response times for HP Care Pack Services may vary depending on your geographic location. Service starts from date of hardware purchase. Restrictions and limitations apply. HP Care Pack Services extend service contracts beyond the standard warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at www.hp.com/po/lookuptool. Additional HP Care Pack Services information by product is available at www.hp.com/hps/carepack.
- 4. DVI dual-link cable sold separately.
- 5. Sold separately or purchased as an optional feature.

© Copyright 2012. Hewlett-Packard Development Company, L.P.

The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. To learn more visit www.hp.com

August 2012